



MOORING CHAIN



Hot Galvanized, Grade 43, Long Link
Not to be used for hoisting or lifting.

Nominal Size		Inside Dimensions (max.)				Working Load Limit		Weight per 100 ft.	
in.	mm.	Length		Width		kg.	lbs.	kg.	lbs.
		in.	mm.	in.	mm.				
3/8"	10.0	1.63	41.5	0.66	16.8	1,837	4,050	66.2	146
1/2"	13.0	2.02	51.3	0.88	22.4	3,129	6,900	115.7	255
5/8"	16.0	2.55	64.8	.94	23.9	4,422	9,750	171.4	378
3/4"	20.0	2.99	76.0	1.05	26.7	5,261	11,600	239.5	528




BigBlue™ ANCHORS

MUSHROOM ANCHORS

Size in lbs.				
25	50	75	100	150
200	250	300	350	400
500	600	800	1000	2,000

PYRAMID ANCHORS

Size in lbs.		
150	200	250
300	350	400
500		



BLUE-PIN™

GALVANIZED SCREW PIN ANCHOR SHACKLES



HOT DIPPED GALVANIZED FORGED SWIVELS

•These swivels are positioning devices



ThreadTight design pin threads for tight, wiggle free security
Larger pin handle hole to accommodate larger tightening tool
Marked with Size and Working Load Limit in Tons.
Forged Heat Treated with Alloy Pins.
Federal Specifications RR-C-271D.



MOORING BUOYS

Shackle nest and 3" Thru-Tube design.
Rotationally molded 1/4" polyethylene, closed cell poly fill. 18" AND 24". Built to last!

Same day shipping
Lift gate service
Consistent pricing
Proven quality
Stocking warehouse
Dependable supply